



STONETECH® DEEPKLENZ™

DS-111.2-0415

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

STONETECH® DEEPKLENZ™

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 235

Toll Free: 1.800.243.4788, ext. 235

Fax: +1.203.393.1684

Website: www.laticrete.com

3. PRODUCT DESCRIPTION

High performance, ready-to-use water based cleaner for use over tile, grout, natural and artificial stones as well as many more surfaces. STONETECH DEEPKLENZ is formulated to easily power through and remove deep and stubborn grease, dirt, and food stains.

Uses

- Removes stains and dirt. Especially from grout and porous stone
- Removes grime, greases, oils, and other organic compounds.
- Easily cleans kitchen & food stains

Advantages

- High performance, ready-to-use cleaner
- Professional strength formulation
- Easily removes deep & stubborn grease, oils, and food stains

Suitable Substrates

Tile, grout, marble, granite, travertine and artificial stone as well as metal and plastic surfaces.

Packaging

24 oz. (709 mL) spray bottle (ready-to-use)/ 12 per case

Approximate Coverage

- 50-300 ft²/gal (4.6-27.8 m²) depending on surface and contamination level.

Shelf Life

1 year if left in an unopened container

Protect from freezing

Limitations

- May affect soundness of some paints.
- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE® Waterproofing Membrane (see Section 10 FILING SYSTEMS).

Cautions

Consult MSDS for more safety information.

- EYE: Mildly irritating to the eyes
- SKIN: No skin irritation expected. May aggravate existing dermatitis.
- INHALATION: Breathing mist may cause mild irritation to upper respiratory tract.
- INGESTION: None known. May cause nausea, abdominal discomfort or diarrhea.
- CHRONIC EFFECTS OF OVEREXPOSURE: Repeated prolonged skin contact may produce irritation.
- OTHER HEALTH EFFECTS (MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE): People sensitive to sulfur compounds can experience aggravated skin irritation.
- Keep out of reach of children.

4. TECHNICAL DATA

Physical Properties

| | |
|------------------|---|
| Form | Liquid |
| Specific Gravity | 1.01 |
| HMIS Rating | Health 1 Flammability 0 Reactivity 0 PP=B |
| Flash Point | Will not flash |
| Freeze Point | 32°F (0°C) |
| pH | 10.5 |

5. INSTALLATION

Read entire label before using. Use only as directed. Test in a small inconspicuous area to determine required results. Be sure all surfaces to be cleaned are swept or vacuumed to remove loose debris. Avoid skin and eye contact with product. Wear protective eyewear, gloves, long sleeves, and long pants while handling concentrate. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area during application and drying.

Application

Temperature range must be between 40-100°F (4-38°C).

1. Apply sufficient material to thoroughly wet the surface.
2. Allow STONETECH® DEEPKELNZ™ to work on the surface for 5-10 minutes (do not allow product to dry on the surface)
3. Lightly scrub with stiff bristle brush to remove the surface contaminants.
4. Rinse and wipe surface with clean cloth and warm water.

*Heavy soiled areas may require a second application.

6. AVAILABILITY AND COST

Availability

LATICRETE® and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

www.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

8. MAINTENANCE

None required

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service

Hotline:

Toll Free: 1.800.243.4788, ext. 235

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at

www.laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at

www.laticrete.com. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty

DS 663.0: HYDRO BAN®

DS 236.0: 9235 Waterproofing Membrane

LATICRETE International, Inc.
One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com
©2015 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.