

# DUPONT™ STONETECH® PROFESSIONAL ENHANCER PRO™ SEALER

## TECHNICAL DATA SHEET



### PRODUCT BENEFITS

- Enriches color
- Protects against water and oil-based stains
- Interior and exterior use, weather resistant
- Solvent-based formula

### RECOMMENDED SURFACES

Natural stone such as limestone, slate, travertine, sandstone, flagstone, tumbled stone, flamed and textured stone, and bluestone.

### AVAILABLE SIZES

Pint, Quart, Gallon\*, 5 Gallon\*

\*Sizes not available in all areas.

### COVERAGE

Up to 450 sq ft per gallon, depending on porosity of stone.

### EXPECTED WEAR

Up to 5 years.

### TECHNICAL INFORMATION

Form:	Liquid
Specific Gravity:	0.80
HMS Rating:	2,3,1
Flash Point:	83 °F (28.3 °C)

### VOC CONTENT

629 g/L

The DuPont™ StoneTech® Professional product line complies with all federal, state and local VOC regulatory requirements.

### DIRECTIONS

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean, free of waxes, coatings, and previous sealers, and is dry for 24–72 hours. Surface must remain dry and free from moisture for the entire cure period. Surface temperature should be between 50 °F and 80 °F (10 °C and 26.7 °C). Ensure that the area is well-ventilated during application and until the surface is dry. Keep children and pets out of the area until treated surface is dry.

1. Mask off any surfaces not intended to be treated.
2. Liberally apply an even coat using a paint pad, roller, brush, or pump-up garden sprayer. Do not use a power sprayer, towel, or sponge for application. Do not thin before using. See Method of Application for more instructions.
3. Allow sealer to penetrate surface for 15–20 minutes. Denser material may require more time to penetrate. DO NOT ALLOW EXCESS SEALER TO DRY ON SURFACE. Failure to remove excess sealer from surface will result in residue that may need to be mechanically removed.
4. Thoroughly wipe surface with multiple dry cloths to remove all remaining sealer.
5. Additional coats may be needed for porous, absorbent surfaces or if a darker appearance is required. Sealer should be applied one hour after initial application, as directed in steps 2–4.
6. Full cure is achieved after 24–72 hours. Avoid foot traffic for 6–8 hours after application. If foot traffic must resume sooner, cover the floor with red rosin paper to protect it until full cure has been achieved. Red rosin paper is not needed to apply second coat.
7. Rags and equipment that are wet with product may be flammable. Clean up promptly after job is complete. Clean equipment with mineral spirits and allow to dry in a well-ventilated area. Allow rags to dry in a well-ventilated area out of the reach of children and pets. When dry, dispose of in accordance with local waste disposal regulations.

### STORAGE AND HANDLING INSTRUCTIONS

**WARNING: FLAMMABLE.** Keep away from heat, sparks, and open flames. HARMFUL OR FATAL IF SWALLOWED. Do not ingest. HARMFUL VAPORS. Avoid prolonged exposure to vapors. Use only in a well-ventilated area. For spray application, use a pump-up garden sprayer. DO NOT USE A POWER SPRAYER. Use a respirator if unsure that work area is well-ventilated. A NIOSH-approved respirator with a combination HEPA/organic vapor cartridge is recommended. Follow respirator manufacturer's instructions for use. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Avoid contact with eyes and skin. Wear solvent-resistant gloves such as nitrile gloves. KEEP OUT OF THE REACH OF CHILDREN. Do not store above 100 °F/38 °C. Do not mix with other chemicals. Do not release to natural waterways.

### METHOD OF APPLICATION

For small jobs, use a paint pad, roller, or brush. For larger jobs, use a pump-up garden sprayer available at your local garden center, hardware store, or home improvement center. Do not use a power sprayer. Power sprayers create a significant amount of overspray, resulting in wasted product and the need for additional clean-up. A pump-up garden sprayer will reduce the potential for over-exposure to vapors and produce better results. Distribute sealer evenly over entire surface. Uneven penetration will result in blotchy appearance.

### EMERGENCY/FIRST AID PROCEDURES

**Ingestion:** Do not induce vomiting. Call poison control center. Call a physician.

**Eye Contact:** Flush thoroughly with water for at least 15 minutes. Call a physician if eye irritation persists.

**Skin Contact:** Wash skin with mild soap and water. Call a physician if skin irritation persists. Launder affected clothing before re-wearing.

**Inhalation:** Remove affected person to fresh air. Call a physician if irritation, nausea, dizziness or respiratory problems persist.

DuPont™ StoneTech® Professional  
2520 Barrington Court  
Hayward, CA 94545

Technical Support: 888-786-6343  
Customer Service: 877-786-6383

www.stonetechpro.com



The miracles of science™

The information is furnished free of charge and based on information that DuPont believes to be generally reliable and accurate. Individual facts and circumstances may differ. It is intended for your use at your own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Copyright © 2014 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™, StoneTech®, and Enhancer Pro™ are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

K-20517-2 (03/14)

PROTECT

CLEAN

TRANSFORM