FILACR10 **EPOXY GROUT HAZE REMOVER**





PORCELAIN GLAZED CERAMIC TILES GLASS MOSAICS POLISHED OUARRY

TILES



WHAT IT'S FOR

- Effectively removes epoxy grout haze
- Ideal for non-absorbent materials such as porcelain, glazed ceramic tiles and glass mosaics.

ADVANTAGES

- Its viscosity makes it easy to apply even to vertical surfaces
- It also gives good results with old
- stubborn residues.
- It respects the material
- It is a water-based cleaner
- Easy to apply
- Pleasant almond fragrance

COVERAGE

With one litre (1,06 QT):

2-4 m² (21/43 sq ft)

"Coverage rates are approximate and refer to a single coat of the product"

HOW IT'S USED

Ready to use: no dilution necessary

Application

Before cleaning with FILACR10, wait for the whole reaction time of the grout. Shake before use. Apply directly to the surface to be cleaned using a large flat paintbrush, perfectly covering all residues of epoxy, especially on vertical areas.

Leave for about 30 minutes. Rub with an abrasive sponge, even using a spatula to remove larger residues. A single brush machine fitted with the most appropriate disc can be used for floors. Rinse thoroughly. For more stubborn residues, repeat the same procedure, leaving the product to work for longer.

Caution:

Always test on a small area of the surface to check the material's resistance and find out optimum waiting times for best results. Do not use on absorbent materials. Do not use on wood. Do not use on methacrylate surfaces. Check the resistance of metal surfaces to the product before use.

irregular or irritation persists seek medical attention.

The information above reflects our latest technical know-how and is the outcome of ongoing laborato-

ry research and testing. However, some factors are beyond our control. It is essential to integrate our

suggestions with your own on-site preliminary tests

Fila accepts no liability for improper use of its products.

TECHNICAL INFORMATION

Odour: distinctive solvent odour

Appearance: viscous liquid Color: yellow to brown

Density: 1.01 kg/l pH: 12.7

and checks.

Packaging

1 liter (1.06 qt) flasks in box of 12.

PRECAUTIONS

 Keep out of the reach of children. • Dispose of the container properly after use.

TEMPERATURE

Storage temperature: between 41° F (5° C) and 86° F (30° C). Must be applied to material at temperatures between 41° F (5° C) and 86° F (30° C).

DO/LB 14

LABELLING CORROSIVE

Warning: DANGER! Hazard statements: CASUSES BURNS TO SKIN AND EYES Precautionary statements: Product mists can burn respiratory tract and will cause burns if swallowed. Keep Out of the Reach of Children. Store in a locked area. Contains sodium hydroxide. Wear rubber gloves and safety glasses or goggles. First aid: In case of eye contact, flush eyes with running water for 15 minutes. Get immediate medi-cal assistance. On skin – Flush with running water. Remove contaminated clothing. If irritation persists or burns are present get medical assistance. If swallowed obtain immediate medical attention. Do not induce vomiting. If inhaled, remove to fresh air. If breathing is



REV. 01 - 04/12/2014