

PERMACOLOR® SELECT/PERMACOLOR GROUT

United States Patent No.: 6,784,229 (and other Patents).

TILE SIZE	JOINT WIDTH				
	1/16"	1/8"	1/4"	3/8"	1/2"
1 x 1 x 1/4"	100	51	28	20	16
2 x 2 x 1/4"	196	100	51	36	28
4 1/4 x 4 1/4 x 5/16"	331	167	85	57	44
6 x 6 x 1/2"	291	146	74	50	38
12 x 12 x 3/8"	774	388	195	131	99
13 x 13 x 3/8"	839	420	211	141	107
16 x 16 x 3/8"	1032	517	259	174	131
18 x 18 x 3/8"	1160	581	292	195	147
	1.5 mm	3 mm	6 mm	9 mm	12 mm
25 x 25 x 6 mm	10.2	5.3	2.8	2.0	1.6
50 x 50 x 6 mm	20.1	10.2	5.3	3.6	2.8
106 x 106 x 7.5 mm	33.8	17.0	8.6	5.8	4.4
150 x 150 x 12 mm	29.8	15.0	7.6	5.2	3.9
300 x 300 x 9 mm	79.4	39.8	20.0	13.4	10.1
325 x 325 x 9 mm	86.0	43.1	21.6	14.5	10.9
400 x 400 x 9 mm	105.8	53.0	26.6	17.8	13.4
425 x 425 x 9 mm	112.4	56.3	28.2	18.9	14.2

Approximate ft² (m²) coverage per 25 lb (11.3 kg) unit.

PLASMA™

TILE SIZE	JOINT WIDTH					
	1/16"	1/8"	3/16"	1/4"	3/8"	1/2"
1 x 1 x 1/4"	53	27	19	15	11	9
2 x 2 x 1/4"	104	53	36	27	19	15
6 x 6 x 1/2"	155	78	52	39	26	20
12 x 12 x 3/8"	412	206	138	104	70	52
13 x 13 x 3/8"	446	224	149	112	75	57
18 x 18 x 3/8"	617	309	206	155	104	78
24 x 24 x 3/8"	822	412	274	206	138	104
	1.5 mm	3 mm	6 mm	9 mm	12 mm	
25 x 25 x 6 mm	4.9	2.5	1.7	1.4	1.0	.83
50 x 50 x 6 mm	9.6	4.9	3.3	2.5	1.7	1.4
150 x 150 x 12 mm	14.4	7.2	4.8	3.6	2.4	1.8
300 x 300 x 9 mm	38.3	19.1	12.8	9.6	6.5	4.8
325 x 325 x 9 mm	41.4	20.8	13.8	10.4	7.0	5.3
450 x 450 x 9 mm	57.3	28.7	19.1	14.4	9.6	7.2
600 x 600 x 9 mm	76.3	38.3	25.4	19.1	12.8	9.6

1600 UNSANDED GROUT

TILE SIZE	JOINT WIDTH	
	1/16"	1/8"
4 1/4 x 4 1/4 x 5/16"	144	72
6 x 6 x 5/16"	202	102
	1.5 mm	3 mm
106 x 106 x 7.5 mm	14.7	7.4
150 x 150 x 7.5 mm	4.5	3.0

Approximate ft² (m²) coverage per 8 lb (3.6 kg) unit.

GROUT AND SEALANT COLOR GUIDELINES

Grout and sealant samples are guides only. LATICRETE does not warrant color matching to this color chart or to any color guide produced. Actual shade and texture will depend on job site conditions, lighting, installation techniques, and types of tile or stone used; they may vary from this grout color chart, grout color channel kits, and grout color swatch on product packaging. Verify actual appearance and compatibility with a test area before installing. Blend grouts with different control numbers. Follow ANSI A108.10/MMSA Bulletin #9 grouting practices. No claims for color shade variations will be honored.

1500 SANDED GROUT

TILE SIZE	JOINT WIDTH			
	1/16"	1/8"	1/4"	3/8"
1 x 1 x 1/4"	100	51	28	20
2 x 2 x 1/4"	196	100	51	36
4 1/4 x 4 1/4 x 5/16"	331	167	85	57
6 x 6 x 1/2"	291	146	74	50
12 x 12 x 3/8"	774	388	195	131
13 x 13 x 3/8"	839	420	211	141
16 x 16 x 3/8"	1032	517	259	174
18 x 18 x 3/8"	1160	581	292	195
	1.5 mm	3 mm	6 mm	9 mm
25 x 25 x 6 mm	10.2	5.3	2.8	2.0
50 x 50 x 6 mm	20.1	10.2	5.3	3.6
106 x 106 x 7.5 mm	33.8	17.0	8.6	5.8
150 x 150 x 12 mm	29.8	15.0	7.6	5.2
300 x 300 x 9 mm	79.4	39.8	20.0	13.4
325 x 325 x 9 mm	86.0	43.1	21.6	14.5
400 x 400 x 9 mm	105.8	53.0	26.6	17.8
425 x 425 x 9 mm	112.4	56.3	28.2	18.9

Approximate ft² (m²) coverage per 25 lb (11.3 kg) unit.

SPECTRALOCK® PRO PREMIUM GROUT/SPECTRALOCK PRO GROUT

United States Patent No.: 6881768 (and other Patents).

TILE SIZE	JOINT WIDTH					
	1/16"	1/8"	1/4"	3/8"	1/2"	
1 x 1 x 1/4"	41	21	11	8	7	
2 x 2 x 1/4"	80	41	21	15	11	
4 1/4 x 4 1/4 x 5/16"	135	68	35	23	18	
6 x 6 x 1/2"	119	60	30	20	15	
12 x 12 x 3/8"	317	159	80	54	44	
13 x 13 x 3/8"	344	172	87	58	43	
16 x 16 x 3/8"	423	212	106	71	54	
18 x 18 x 3/8"	475	238	119	80	60	
	1.5 mm	3 mm	6 mm	9 mm	12 mm	
25 x 25 x 6 mm	4.2	2.1	1.1	0.8	0.7	
50 x 50 x 6 mm	8.2	4.2	2.1	1.5	1.1	
106 x 106 x 7.5 mm	13.8	6.9	3.5	2.4	1.8	
150 x 150 x 12 mm	12.2	6.1	3.1	2.1	1.6	
300 x 300 x 9 mm	32.3	16.2	8.1	5.5	4.1	
325 x 325 x 9 mm	35.0	17.6	8.8	5.9	4.5	
400 x 400 x 9 mm	43.1	21.6	10.8	7.3	5.5	
450 x 450 x 9 mm	48.5	24.3	12.2	8.1	6.1	

Approximate ft² (m²) coverage per full unit.

SPECTRALOCK 2000 IG

TILE SIZE	JOINT WIDTH		
	1/4"	3/8"	1/2"
4 x 8 x 1 3/16"	29	19	15
6 x 6 x 1/2"	77	52	39
	6 mm	9 mm	12 mm
100 x 200 x 30 mm	2.8	1.9	1.6
150 x 150 x 12 mm	7.2	5.6	4.3

Approximate ft² (m²) coverage per #2 unit.

Calculated coverage indicated is approximate, based on "nominal" tile size, and is provided for purposes of estimation only. Actual coverage will vary depending on job site conditions, actual tile size, and installed grout joint size. Add 10% for waste, spillage, and clean-up, and another 10%–15% when grouting unglazed quarry tile. Expanded coverage tables at www.laticrete.com/coverage.